

Technical specifications

ZS 55⁺-75⁺ - 50-60 HZ

	Working pressure	Frequency	Free Air Delivery ⁽¹⁾				Sound level with canopy ⁽²⁾ , at 600 mbar(e)	
	mbar(e)		Hz	m ³ /hr		cfm		dB(A)
				min.	max.	min.	max.	
ZS 55 A	800	50 Hz	1283	1254	755	738	69	
	1200		1269	1224	747	720		
ZS 55 B	800	50 Hz	1723	1700	1014	1001	69	
	1200		1712	1678	1008	988		

Dimensions (L x W x H): 2288 x 1080 x 1850 mm or 89 x 42 x 72 inch

	Working pressure	Frequency	Free Air Delivery ⁽¹⁾				Sound level with canopy ⁽²⁾ , at 600 mbar(e)	
	mbar(e)		Hz	m ³ /hr		cfm		dB(A)
				min.	max.	min.	max.	
ZS 55 A	800	60 Hz	1569	1545	923	909	71	
	1200		1557	1521	916	895	72	
ZS 55 B	800	60 Hz	2082	2062	1225	1214	71	
ZS 75 B	1200		2072	2042	1220	1202	72	

Dimensions (L x W x H): 2288 x 1080 x 1850 mm or 89 x 42 x 72 inch

(1) Reference conditions:

- Dry air
- Absolute inlet pressure 1 bar(a)
- Cooling and air intake temperature 20 °C
- Nominal working pressure identical to maximum pressure
- Capacity of the compressor package measured according to ISO 1217, Third Edition, Annex C

(2) ± 3 dB(A) according to ISO 2151:2004 and using ISO 9614-2